

---

62243

OFFROAD STANDARD | Halogen headlight lamps



---

Areas of application

- Headlight
- Forestry, agriculture and the construction industry for off-road area

---

Product benefits

- Rugged and versatile
- Excellent reliability and brightness even on the most difficult terrain

---

Product features

- Vibration resistant technology

# Product datasheet

## Technical data

### Electrical data




Power input	100 W <sup>1)</sup>
Nominal voltage	24.0 V
Nominal wattage	100.00 W
Test voltage	28.0 V

<sup>1)</sup> Maximum

### Photometrical data

Luminous flux	2600 lm
Luminous flux tolerance	±15 %

### Dimensions & weight



PK22s  
IEC 7004-47  
DIN 49742  
  
IEC 7005-47  
DIN 49762

Length	42.0 mm
Diameter	12.0 mm
Product weight	6.70 g

### Lifespan

Lifespan B3	50 h
Lifespan Tc	200 h

### Additional product data

Base (standard designation)	PK22s
-----------------------------	-------

### Certificates & standards

ECE category	-
--------------	---

### Country specific categorizations

# Product datasheet

---

<b>Order reference</b>	62243 100W 24V
------------------------	----------------

---

## Product datasheet

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321773999	62243	Folding carton box 1	- x - x -		
4008321774002	62243	Bundle 10	- x - x -		
4008321774019	62243	Shipping carton box 100	245 mm x 145 mm x 140 mm	4.97 dm <sup>3</sup>	985.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Legal advice

Only approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

No ECE approval

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.