

LEDTOUCH DOWNLIGHT 5

Indoor LED spotlights with 5 inch diameter



Areas of application

- Offices
- Shopping malls
- Retail
- Airports
- Hospitals
- Metro stations
- Public areas
- For indoor use only

Product benefits

- Good glare reduction (UGR < 19)
- Even light distribution thanks to Fresnel and micro lenses
- Clear cast shadows (no ghost shadows) due to Chip-On-Board technology

Product features

- Available with different wattages, beam angles and in various sizes
- Lifetime: up to 50,000 h



Product family datasheet

Technical data

Product description	Electrical data		Dimensions & weight			Colors & materials			Capabilities
	Nominal wattage	Mains frequency	Length	Width	Height	Body material	Product color	Cover material	Type of installation
LDTH DL 5 20 W 827 26°	20 W	50/60 Hz	135.0 mm	135.0 mm	160.0 mm	diecast aluminium	light grey (RAL 7035)	PC	recessed
LDTH DL 5 20 W 830 26°	20 W	50/60 Hz	135.0 mm	135.0 mm	160.0 mm	diecast aluminium	light grey (RAL 7035)	PC	recessed
LDTH DL 5 20 W 840 26°	20 W	50/60 Hz	135.0 mm	135.0 mm	160.0 mm	diecast aluminium	light grey (RAL 7035)	PC	recessed
LDTH DL 5 20 W 827 38°	20 W	50/60 Hz	135.0 mm	135.0 mm	160.0 mm	diecast aluminium	light grey (RAL 7035)	PC	recessed
LDTH DL 5 20 W 830 38°	20 W	50/60 Hz	135.0 mm	135.0 mm	160.0 mm	diecast aluminium	light grey (RAL 7035)	PC	recessed
LDTH DL 5 20 W 840 38°	20 W	50/60 Hz	135.0 mm	135.0 mm	160.0 mm	diecast aluminium	light grey (RAL 7035)	PC	recessed
LDTH DL 5 20 W 827 46°	20 W	50/60 Hz	135.0 mm	135.0 mm	160.0 mm	diecast aluminium	light grey (RAL 7035)	PC	recessed
LDTH DL 5 20 W 830 46°	20 W	50/60 Hz	135.0 mm	135.0 mm	160.0 mm	diecast aluminium	light grey (RAL 7035)	PC	recessed
LDTH DL 5 20 W 840 46°	20 W	50/60 Hz	135.0 mm	135.0 mm	160.0 mm	diecast aluminium	light grey (RAL 7035)	PC	recessed

Product description	Type of connection	Country specific categorizations
		Order reference
LDTH DL 5 20 W 827 26°	cable with plug	LDTH DL 520 L26
LDTH DL 5 20 W 830 26°	cable with plug	LDTH DL 520 L26
LDTH DL 5 20 W 840 26°	cable with plug	LDTH DL 520 L26
LDTH DL 5 20 W 827 38°	cable with plug	LDTH DL 520 L38
LDTH DL 5 20 W 830 38°	cable with plug	LDTH DL 520 L38

Product family datasheet

Product description	Type of connection	Country specific categorizations
		Order reference
LDTH DL 5 20 W 840 38°	cable with plug	LDTH DL 520 L38
LDTH DL 5 20 W 827 46°	cable with plug	LDTH DL 520 L46
LDTH DL 5 20 W 830 46°	cable with plug	LDTH DL 520 L46
LDTH DL 5 20 W 840 46°	cable with plug	LDTH DL 520 L46

Product family datasheet

Equipment / Accessories

- Safety cable for reflector included (hole for fixing the cable existing)
-

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.