OSRAM

64215TSP TRUCKSTAR PRO | Halogen headlight lamps



Product benefits

- Tried and trusted in millions of vehicles of well-known automobile manufacturers
- Excellent price/performance ratio
- Impressive brightness and reliable lifetime
- Up to 100 % more light (compared to standard lamps)
- Up to 100 % longer lifetime (compared to standard lamps)
- Suitable for heavy duty applications thanks to very high vibration resistance
- Increased driving safety thanks to better illumination of the road

Product features

- Available for all headlight functions in H1, H3, H4, H7

Technical data

Electrical data

Power input	75 W ¹⁾
Nominal voltage	24.0 V
Nominal wattage	70.00 W
Test voltage	28.0 V

¹⁾ Maximum

Photometrical data

Luminous flux	1750 lm
Luminous flux tolerance	±10 %

Dimensions & weight



Length	59.0 mm
Diameter	12.0 mm
Product weight	12.50 g

Lifespan

Lifespan B3	500 h
Lifespan Tc	1000 h

Additional product data

Base (standard designation)	PX26d
Certificates & standards	

H7

ECE category

Country specific categorizations

Order reference

64215TSP 70W 24

Logistical Data

				-	
Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321785114	64215TSP	Folding carton box 1	58 mm x 34 mm x 34 mm	0.07 dm ³	12.00 g
4008321785121	64215TSP	Bundle 10	69 mm x 58 mm x 172 mm	0.69 dm ³	155.00 g
4008321785138	64215TSP	Shipping carton box 100	356 mm x 129 mm x 186 mm	8.54 dm ³	1727.00 g
4008321785145	64215TSP	Hard Cover Box 2	115 mm x 47 mm x 95 mm	0.51 dm³	109.00 g
4008321785152	64215TSP	Shipping carton box 20	250 mm x 240 mm x 106 mm	6.36 dm ³	1230.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Legal advice

ECE E1 approval

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.