

OTz 30/220...240/24

CV Power supplies 24 V



Areas of application

- Suitable for indoor and outdoor SELV installations
- Outdoor applications only in suitable installations
- Suitable for use in tight, flat luminaires or installation in suspended ceilings

Product benefits

- Versatile scope of application due to output power range of up to 240 W
- Very high efficiency and reliability
- Constant luminous flux for very low and high temperatures due to Smart Power Supply

Product datasheet

Technical data

Electrical data

Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Max. ECG no. on circuit breaker 25 A (B)	-

Dimensions & weight

Length	140.0 mm
Width	45.0 mm
Height	27.5 mm
Product weight	145.00 g

Temperatures & operating conditions

Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	5...85 %

Certificates & standards

Protection class	II
Type of protection	IP20

Logistical data

Temperature range at storage	-40...85 °C
------------------------------	-------------

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899932142	OTz 30/220...240/24	Shipping carton box 20	242 mm x 153 mm x 162 mm	6.00 dm ³	3180.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.